

ROLLANT		620 RC	620 RF
Hitching			
PTO shaft speed	rpm	540	540
Single wide-angle drive shaft with freewheel and cam control		●	○
Single wide-angle universal drive shaft with shear bolt coupling		●	●
Power requirement	hp	80	80
Pick-up			
Width	m	2.10	2.10
DIN pick-up width	m	1.90	1.90
Simple spool valve for raising the pick-up and the knives		●	●
No. of tines per row		32	32
Tine spacing	mm	70	70
Pick-up castor guide wheels		Fixed (oscillating ○)	Fixed (oscillating ○)
Crop feed			
Forced feed with		ROTO CUT	ROTO FEED
Number of knives		7	–
Hydraulic connection			
Simple spool valve for raising the pick-up		●	●
Dual-acting spool valve for tailgate rams		●	●
Crop feed			
Number of compaction rollers		17	17
Automatic dual twine wrapping		●	●
Net wrapping ROLLATEX		●	●
Twine reels in the twine box		6	6
Net rolls		2	2
Adjustable baling pressure on the machine		○	○
Bale ramp		○	○
New chain lubrication		●	●
Bale chamber dimensions			
Width	m	1.22	1.22
Diameter	m	1.50	1.50
Operation			
OPERATOR		●	●
Tyres			
11.5/80-15.3 8PR		●	●
15.0/55-17 10PR		○	○
19.0/45-17 10PR		○	○
Running axle		●	●
Air brakes		○	○
Hydraulic brakes		○	○
Active hydraulic braking system		○	○
Dimensions and weights			
Length	m	5.08	5.08
Width	m	2.47	2.47
Height	m	2.97	2.97
Weight	kg	3470	3250

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual.